

07/28/00
JCE83 U.S. PTO

OSTROLENK, FABER, GERB & SOFFEN, LLP
Attorneys at Law
1180 Avenue of the Americas
New York, New York 10036-8403

(212) 382-0700

Telex
23 6925

Facsimile
(212) 382-0888

Cable
Ostrofaber New York

Express Mail #EL008134051US

Asst. Commissioner for Patents
Washington, DC 20231

OFGS File No. : P/3541-6
Inventor : Kenichi OINOUE
Title : ELECTRONIC CAMERA AND ELECTRONIC CAMERA SYSTEM
Assignee : Olympus Optical Co., Ltd.

Enclosed herewith please find the following documents in the above-identified application for United States Letters Patent:

- 23 Pages of Specification including Abstract and Claims
- 13 Numbered Claims Calculated as 13 Claims for Fee Purposes
- 3 Sheets of Drawing Containing Figures 1 to 3.
- X Declaration and Power of Attorney
- X Priority is Claimed under 35 U.S.C. §119:
- Convention Date August 25, 1999 for Japan Appln. S.N. 11-238683
- X Certified Priority Application
- Verified Statement Claiming Small Entity Status under 37 C.F.R. §1.27.
- X Assignment
- X Return-Addressed Post Card

OFGS Check No. 95920, which includes the fee of \$730.00, calculated as follows:

Basic Filing Fee:	\$ 690.00
Additional Filing Fees:	
Total Number of Claims in Excess of 20, times \$18:	
Number of Independent Claims in Excess of 3, times \$78:	
One or More Multiple Dependent Claims: Total \$260:	
Total Filing Fees or	690.00
Total Filing Fee Reduced 50% for Small Entity:	
Assignment Recording Fee: \$40	40.00
TOTAL Filing Fee and Assignment Recording Fee:	<u>\$ 730.00</u>

In the event the actual fee is greater than the payment submitted or is inadvertently not enclosed, or if any additional fee during the prosecution of this case is not paid, the Patent and Trademark Office is authorized to charge the underpayment to Deposit Account No. 15-0700.

EXPRESS MAIL CERTIFICATE

Respectfully submitted,

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee (mail label #EL008134051US) in an envelope addressed to: Asst. Commissioner for Patents, Washington, D.C. 20231, on July 28, 2000:

Dorothy Jenkins

Name of Person Mailing Correspondence

Dorothy Jenkins

Signature

July 28, 2000

Date of Signature

Steven I. Weisburd
Steven I. Weisburd

Registration No.: 27,409

OSTROLENK, FABER, GERB & SOFFEN, LLP
1180 Avenue of the Americas
New York, New York 10036-8403
Telephone: (212) 382-0700

JCE83 U.S. PTO
09/02/00
07/28/00

TITLE OF THE INVENTION

ELECTRONIC CAMERA AND ELECTRONIC CAMERA SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 11-238683, filed August 25, 1999, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

10 The present invention relates to an electronic camera and an electronic camera system, which comprises the electronic camera and communication unit attached thereto.

15 In recent years, an electronic camera, which does not require the silver salt film, is widely widespread, and the memory card, which encloses flash ROM, is used in many models of the electronic camera as the record medium. And, as an improvement of the integration of the semiconductor memory in recent years, the capacity
20 of image data to be recorded on the memory card has been greatly improved.

25 However, even if it is an environment of which the record capacity of the memory card has been improved, the capacity of the memory card, which can be used in the electronic camera purchased, is determined according to the model of the electronic camera, and image data cannot be recorded exceeding the capacity of

memory card even when the memory card has the large capacity. Therefore, when an electronic camera is carried, it is necessary to ordinarily prepare the spare memory card beforehand.

5 In the state that no spare memory card is carried and only one memory card installed in an electronic camera can be used, it takes a great deal of times, since the image file recorded on the memory card is transferred and recorded to, for example, the personal
10 computer of a portable type by connecting it with the electronic camera, or is temporarily transferred and recorded to the personal computer of own house or the server of the computer network joined by further connecting a digital mobile telephone and PHS (Personal
15 Handyphone System: second generation cordless telephone system) through the personal computer.

BRIEF SUMMARY OF THE INVENTION

An object of the present invention is to provide an electronic camera system, which can execute
20 continuously shooting operation without limiting the capacity of the record medium of electronic camera and inconvenient operation, etc.

The electronic camera system according to the present invention is characterized by comprising:
25 an electronic camera including a record medium which records an image information obtained by a shooting, detection means which detects that a memory capacity

of the record medium becomes a predetermined value,
and a first interface which transmits and receives
information; and a communication unit including
wireless communication means which can transmits
5 an image file, transmission control means to transmit
the image information recorded on the record medium by
the wireless communication means based on a detection
signal from the detection means, and a second interface
which transmits and receives the information with
10 the first interface of the electronic camera.
The preferred manners of the electronic camera system
according to the present invention are as follows.

(1) The electronic camera further includes first
setting means to adjust a memory capacity of the record
15 medium detected by the detection means.

(2) The communication unit has measurement means
to measure a communication environment by the wireless
communication means, and the electronic camera further
includes second setting means to adjust an amount of
20 the image file to be continuously transmitted according
to the communication environment measured by the
measurement means.

(3) The transmission control means can connect
a plurality of wireless communication systems with
25 different rate systems.

(4) In (3), one of the electronic camera or
the communication unit has selection means to select

a wireless communication system to be connected based on at least one of the capacity of the image file to be transmitted or a rate system.

5 An electronic camera according to the present invention is characterized by comprising: a record medium which makes an image obtained by a shooting a file and records it; wireless communication means which can transmits and receives an image information recorded on the record medium; setting means to set
10 a memory capacity recorded on the record medium; detection means to detect that a memory capacity recorded on the record medium becomes a capacity set by the setting means; and transmission and reception control means to transmit and receive recorded
15 information recorded on the record medium with the wireless communication means based on a detection signal from the detection means. The preferred manners of the electronic camera according to the present invention are as follows.

20 (1) The wireless communication means and the transmission control means are made a unit, and the unit can be attached to the electronic camera.

(2) The transmission and reception control means includes position registration means to secure a
25 position to a nearest communication base station automatically, and controls to transmit a recorded information to the nearest communication base station.

(3) The transmission and reception control means includes judgment means to judge whether the recorded information can be transmitted to a nearest communication base station, and the setting means decreases the set memory capacity when the judgment means judges that it is impossible to transmit the recorded information.

(4) The transmission and reception control means includes judgment means to judge whether the recorded information can be transmitted to the communication base station, and the setting means resets the set memory capacity when the judgment means judges that it is impossible to transmit the recorded information.

(5) The transmission and reception control means includes means to receive a communication completion signal and means to delete information to be transmitted from the record medium after the communication completion signal is received.

(6) The transmission and reception control means can be connected with a plurality of wireless communication systems with different rate systems.

(7) In (6), the transmission and reception control means includes selection means to select a wireless communication system to be connected based on at least one of capacity of the image information to be transmitted or the rate systems.

In the electronic camera and the electronic camera system according to the present invention, when the

capacity of the image file recorded on the record medium installed in the electronic camera reaches a predetermined value (threshold value), this value is detected and the image file recorded on the record medium is transmitted by the wireless communication means. As described above, since the recorded image file is automatically transferred to, for example, the personal computer of own house, the laboratory which is contracted beforehand, or the server of the computer network joined beforehand, etc., when the record capacity of the record medium becomes a predetermined value, the shooting operation can be continuously executed when the camera is used in the communication area where the above-mentioned communication unit can communicate, even when the capacity of the record medium is small and the spare record medium is not carried.

In the above-mentioned configuration, since the threshold value can be adjusted, it is possible to freely set whether information is transferred with many times by dividing information into small units or with few times by a large unit according to the system requirements and the record capacity of the record medium etc.

In addition, in the above-mentioned configuration, since the communication environment by the wireless communication means is measured and the amount of the

image file to be transmitted is adjusted according to this measurement result, the image file can surely be transmitted by limiting continuous transmission time according to the electric wave environment.

5 Since the using wireless communication means can be selected from capacity of the transmitted image file and the plurality of rate systems, the transmission can be executed by automatically selecting a cheaper communication means according to the capacity of the
10 transmitted image file.

 Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects
15 and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

 The accompanying drawings, which are incorporated
20 in and constitute a part of the specification, illustrate presently preferred embodiments of the invention, and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of
25 the invention.

 FIG. 1 is a perspective view, which shows an external configuration of electronic camera system

according to an embodiment of the present invention;

FIG. 2 is a block diagram, which shows a circuit configuration according to this embodiment; and

FIG. 3 is a flow chart, which shows a processing
5 content of an operation according to this embodiment.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, an embodiment will be explained
referring to the drawings when the present invention is
applied to the electronic camera system using a digital
10 mobile telephone.

FIG. 1 is figure, which shows an external configuration, and shows electronic camera 1 and communication unit 2 attached to the bottom of electronic camera 1.

Electronic camera 1 comprises release switch (SW)
15 11, guide panel 12 with LCD panel of segment type, and various mode switches (SW) 13 which set and instruct each operation mode such as the image transfer mode described later on rectangular parallelepiped camera housing 10.

20 Card slot cover 14 which covers the slot (not shown in the figure) which inserts the memory card which is the record medium of this electronic camera 1 is installed with free opening and shutting from a right side of camera housing 10 to front surface
25 thereof, and in addition, optical viewfinder window 15, lens mirror cylinder 16, flash luminescence section 17, and the self-timer lamp 18 are properly set in front of

camera housing 10.

On the rear surface of camera housing 10, the power supply switch, color TFT-LCD panel which operates electronic viewfinder (EVF), and the optical
5 viewfinder, etc. are provided (here, not shown in the figure).

Communication unit 2 with a thin plate of same size substantially as the bottom of electronic camera 1 are attached to the bottom of electronic camera 1.

10 This communication unit 2 is attached by combining the screw in the hole for tripod attachment formed in the bottom of electronic camera 1. Therefore, communication unit 2 cannot perform communication and operation by the voice as a general digital mobile
15 telephone, but the image data file can be transferred from electronic camera 1 with the connector (not shown in the figure here). As a result, since communication unit 2 registers the position of the nearest public base station by the position registration processing
20 automatically executed along with movement, the wireless connection is performed with the public circuit net, the image data file received from electronic camera 1 is transferred to the personal computer of own house, the laboratory which is
25 contracted beforehand or, and the data server of the computer network service joined beforehand.

FIG. 2 is a figure, which shows a circuit

configuration of above-mentioned electronic camera 1 and communication unit 2.

5 An optical image of the subject is imaged at the record mode and optical lens system 21 images the optical image on CCD 22 in electronic camera 1. After the output of this CCD 22 is digitalized by each pixel unit in A/D converter 23, the output thereof is sent to buffer memory 24.

10 Buffer memory 24 saves a plurality of image data with the bit map form. The individual image data saved in buffer memory 24 is compressed at any time by the predetermined file format, for instance, by JPEG in image processing section 25, made to a file, sent to memory control circuit 26, and thereafter, written on
15 memory card 27 which is the record medium of this electronic camera 1 detachably installed.

 At this time, image data, in which the number of pixels is greatly decreased, is read from buffer memory 24 to display section 29, and display section 29
20 displays and drives the TFT-LCD panel as the electronic viewfinder provided to the rear surface of above-mentioned camera housing 10 based on this image data, and the content imaged by CCD 22 is displayed in real time.

25 On the other hand, at the reproduction mode, the file of the image data recorded on memory card 27 is selectively read with memory control circuit 26,

expanded by image processing section 25 according to the procedure opposite to the above-mentioned compression processing, and saved in buffer memory 24 after developing the image data to the bit map form.

5 The image data saved in this buffer memory 24 is read to display section 29, and the reproduction of the recorded image is displayed by driving TFT-LCD panel with display section 29 based on this image data.

Controller 28 controls all operations of CCD 22,
10 A/D converter 23, buffer memory 24, image processing section 25, memory control circuit 26, and display section 29.

This controller 28 performs the operation control of all circuits of electronic camera 1. Controller 28
15 is also connected key switch (SW) section 30, guide panel 12, and interface section (I/F) 31 again, and controls these.

Key switch section 30 includes release switch 11, various mode switches 13, and the power supply switch, etc., and sends the operation signals directly to
20 controller 28.

Guide panel 12 displays various operation states of electronic camera 1 based on the driving control signals from controller 28.

25 Interface section 31 performs the transmission and reception of data between controller 28 and communication unit 2.

On the other hand, communication unit 2 has interface section (I/F) 41 for data communication with electronic camera 1, controller 42, which performs this operation control of whole communication unit 2, data
5 buffer 43, communication controller 44, which performs transmission and reception of electric wave in, for example, 1.5 G[Hz] band, as digital mobile telephone, and antenna 45 connected with this communication controller 44, and the data, which is sent from
10 interface section 31 of electronic camera 1, is sent to controller 42 through interface section 41.

Controller 42 always executes the position registration processing with the nearest base station which accompanies movement with communication
15 controller 44 and antenna 45, when image data is sent from electronic camera 1, after holding it in data buffer 43, the image data is transmitted one by one by communication controller 44 from antenna 45 to the base station in which the position is registered.

20 Next, operation of the above-mentioned embodiment will be explained.

FIG. 3 shows the a processing content at the record mode on the side of electronic camera 1 to which communication unit 2 is attached as one unit. First,
25 whether the capacity of the image data file recorded on memory card 27 exceeds the predetermined constant value or not (step S01) and whether release switch 11 is push

or not (step S02) are judged, repeatedly. In step S01 and step S02, if the judgment result is "N", the procedure is waited until the judgment result becomes "Y".

5 That is, in step S01, when the record capacity of memory card 27 is, for example, 8 MB, and the predetermined constant value becomes 6 MB, that is, when remainder capacity of memory card 27 becomes below 2 MB, it is judged "Y".

10 When there is a push operation of release switch 11 to instruct the shooting, it is judged "Y" in step S02, the distance from electronic camera 1 to the subject image at that time is measured, the proper exposure is measured, and also the proper white balance
15 is adjusted, thereafter flash luminescence section 17 emits light if necessary properly and the shooting is executed (step S03).

 The image data obtained from CCD 22 by the shooting is temporarily stored in buffer memory 24
20 after each configuration pixel is digitalized with A/D converter 23, and the data compression is performed based on JPEG in image processing section 25 and is made to the file.

 And, the obtained image data file is recorded on
25 memory card 27 with memory control circuit 26 (step S04). Here, controller 28 manages record of memory card 27 at the same time as this operating. Whether it

is possible to shoot the number of images in which the image of the picture quality mode is set at that time, is calculated at remaining capacity, and general processing such as displaying the result with guide panel 12, etc. are executed. In addition, as shown in step S01, controller 28 judges whether the total amount of the recorded image data file exceeds a constant value by newly recording the image data file on memory card 27.

When it is judged that the record capacity of memory card 27 exceeds the predetermined constant value in step S01, it is judged whether the mode, in which the image data file recorded on memory card 27 is transferred if necessary by communication unit 2, is set by operation of above-mentioned various mode switches 13 (step S05).

In step S05, this processing ends, and processing is returned to processing from step S01, when the image transfer mode is not set. In step S05, when the image transfer mode is set, it judges whether the communication to transmit image data is possible by using communication unit 2 (step S06).

In step S06, it is judged whether communication unit 2 can perform the position registration processing to the nearest base station. When it is judged the power supply of communication unit 2 is continuously, turned on, the position registration processing is

automatically executed when electronic camera 1 to which communication unit 2 is attached moves. It can be considered to turn on the power supply of communication unit 2 automatically to avoid useless power consumption, when it is judged that the image transfer mode is set in step S05. In such a case, this judgment is executed by performing the position registration processing again after the power supply is turned on.

When communication unit 2 cannot register the position to the nearest base station in step S06, since the data communication cannot be performed, this processing is ended once and processing is returned to processing from step S01 again. When the position can be registered in step S06, it is confirmed whether it is possible to obtain enough electric field intensity, and execute the data communication in a steady state (step S07).

In step S07, only when it is judged that the obtained electric field intensity is low and it is difficult to continue a steady data communication, it is reset such that the amount of the image data file to be continuously transferred is decreased (step S08).

This is processing to transmit the image data file surely by decreasing the amount of the image data file transferred at a time and limiting the time continuously transmitted, when the radio environment is bad.

Thereafter, dial is performed to connect the line

with own house, laboratory which is contracted or server of computer network service joined, which transfer destination of image data file (step S09).

5 And, it is judged whether the line is connected as a result of the dial (step S10). Since the processing for the data transfer cannot be continued any more when the line cannot be connected, this processing is ended above once, and processing is returned to step S01.

10 When line can be connected, the image data file is read from the memory card 27 one by one and is transferred and transmitted to the connection destination until it is judged that the set amount of data has been transmitted (steps S11 and S12).

15 And, when it is judged that the transfer is completed, it is judged whether the transfer is succeeded, that is, the transfer is completed without error according to the content of the signal of the confirmation of the data reception of the transfer destination (step S13), and only when it is judged that
20 the transfer succeeded, data, which is transferred among the image data file recorded in memory card 27, is erased, assuming that the transferred image data file is surely recorded at transfer destination (step S14). A series of processing is ended above and
25 returns to processing from step S01 again.

Thus, when the record capacity of memory card 27, which is the record medium, reaches a constant value,

since the recorded image data file is automatically transferred and recorded to the predetermined device such as, for example, the personal computer of own house, the laboratory which is contracted or the server of the computer network service etc., in a case that the camera is used in the communication area where communication unit 2 can communicate, the shooting operation can be continued at ease, even when the record capacity of memory card 27 is small and it is time when the spare memory is not carried.

It is desirable the value to judge whether the above-mentioned transfer is performed or not can be freely and variably set according to the record capacity of memory card 27, the radio environment of the use place, and the use object of electronic camera 1, etc. Since information is transferred with many times by dividing information into small units or with few times by a large unit according to the system requirements and the record capacity of the record medium etc., the judgment value can be set by a user so that it may be easy to use most for users, and the data transfer may obstruct the shooting operation.

In the above-mentioned embodiment, it is explained that communication unit 2 is a digital mobile telephone. If a digital mobile telephone and PHS (Personal Handyphone System: second generation cordless telephone system) terminal unit can be used by

switching them with one for example, it is possible to set such that the accounted amount becomes smallest account according to each rate system

5 Additionally, the present invention can be carried out by modifying the embodiment described above within the scope of the invention.

WHAT IS CLAIMED IS:

1. An electronic camera system comprising:

an electronic camera including a record medium
which records an image information obtained by a
5 shooting, detection means which detects that a memory
capacity of said record medium becomes a predetermined
value, and a first interface which transmits and
receives information; and

a communication unit including wireless
10 communication means which can transmits an image file,
transmission control means to transmit the image
information recorded on said record medium by said
wireless communication means based on a detection
signal from said detection means, and a second
15 interface which transmits and receives the information
with said first interface of said electronic camera.

2. The electronic camera system according to
claim 1, wherein said electronic camera further
includes first setting means to adjust a memory
20 capacity of said record medium detected by said
detection means.

3. The electronic camera system according to
claim 1, wherein

said communication unit has measurement means to
25 measure a communication environment by said wireless
communication means, and

said electronic camera further includes second

setting means to adjust an amount of the image file to be continuously transmitted according to the communication environment measured by said measurement means.

5 4. The electronic camera system according to claim 1, wherein said transmission control means can connect a plurality of wireless communication systems with different rate systems.

10 5. The electronic camera system according to claim 4, wherein one of said electronic camera or said communication unit has selection means to select a wireless communication system to be connected based on at least one of the capacity of the image file to be transmitted or a rate system.

15 6. An electronic camera comprising:
a record medium which makes an image obtained by a shooting a file and records it;

wireless communication means which can transmits and receives an image information recorded on said record medium;

20 setting means to set a memory capacity recorded on said record medium;

detection means to detect that a memory capacity recorded on said record medium becomes a capacity set by said setting means; and

25 transmission and reception control means to transmit and receive recorded information recorded on said record medium with said wireless communication

means based on a detection signal from said detection means.

7. The electronic camera according to claim 6, wherein

5 said wireless communication means and said transmission control means are made a unit, and
 said unit can be attached to said electronic camera.

8. The electronic camera according to claim 6,
10 wherein said transmission and reception control means includes position registration means to secure a position to a nearest communication base station automatically, and controls to transmit a recorded information to the nearest communication base station.

15 9. The electronic camera according to claim 6, wherein

 said transmission and reception control means includes judgment means to judge whether the recorded information can be transmitted to a nearest
20 communication base station, and

 said setting means decreases the set memory capacity when said judgment means judges that it is impossible to transmit the recorded information.

25 10. The electronic camera according to claim 6, wherein

 said transmission and reception control means includes judgment means to judge whether the recorded

information can be transmitted to the communication base station, and

said setting means resets the set memory capacity when said judgment means judges that it is impossible
5 to transmit the recorded information.

11. The electronic camera according to claim 6, wherein said transmission and reception control means includes means to receive a communication completion signal and means to delete information to be
10 transmitted from the record medium after the communication completion signal is received.

12. The electronic camera according to claim 6, wherein said transmission and reception control means can be connected with a plurality of wireless
15 communication systems with different rate systems.

13. The electronic camera according to claim 12, wherein said transmission and reception control means includes selection means to select a wireless
20 communication system to be connected based on at least one of capacity of the image information to be transmitted or the rate systems.

ABSTRACT OF THE DISCLOSURE

An electronic camera system comprises an electronic camera including a record medium which records an image information obtained by a shooting,
5 detection means which detects that a memory capacity of the record medium becomes a predetermined value, and a first interface which transmits and receives information, and a communication unit including
10 wireless communication means which can transmits an image file, transmission control means to transmit the image information recorded on the record medium by the wireless communication means based on a detection
15 signal from the detection means, and a second interface which transmits and receives the information with the first interface of the electronic camera.




FIG. 1




FIG. 2




FIG. 3

Declaration Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の横に記載された通りです。

My residence, post office address and citizenship are as stated below next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者である（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

電子カメラ及び電子カメラシステム

ELECTRONIC CAMERA AND ELECTRONIC CAMERA SYSTEM

上記発明の明細書（下記の欄で×印がついていない場合は、本書に添付）は、

The specification of which is attached hereto unless the following box is checked:

☐ 月 日に☐ was filed on _____ as United States Application Number or PCT International Application Number

提出され米国出願番号または特許協定条約

国際出願番号を _____ とし、

_____ and was amended on

（該当する場合） _____ 月 _____ 日に訂正されました。

_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されたとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration

(日本語宣言書)

私は、合衆国法典第35編第119条(a)-(d)項又は第365条(b)に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

外国での先行出願

Priority Not Claimed

優先権の主張なし

11-238883

JAPAN

25/08/1999

(Number)
(番号)(Country)
(国名)(Day/Month/Year Filed)
(出願年月日)

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)
(出願番号)(Filing Date)
(出願日)(Application No.)
(出願番号)(Filing Date)
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) or 365(c) of any PCT international application designating the United States, listed below and insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT information application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which become available between the filing date of the prior application and the national or PCT international filing date of application:

(Application No.)
(出願番号)(Filing Date)
(出願日)(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)(Application No.)
(出願番号)(Filing Date)
(出願日)(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書で私が行う表明が真実であり、かつ私の入手した情報と私の信じることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰され、そしてそのような故意による虚偽の声明を行えば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration

(日本語宣言書)

委任状: 私は、下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。
(弁理士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Samuel H. Weiner (Reg.No.18,510), Robert C. Faber (Reg.No.24,322), Edward A. Meilman (Reg.No.24,735), Stanley H. Lieberstein (Reg.No.22,400), Steven L. Weisburd (Reg.No.27,409), Max Moskowitz (Reg.No.30,576), Stephen A. Soffen (Reg.No.31,063), James A. Finder (Reg.No.30,173), William O. Gray, III (Reg.No.30,944), Louis C. Dujmich (Reg.No.30,625) and Douglas A. Hiro (Reg.No.31,643).

書類送付先:

Send Correspondence to
Ostrolenk, Faber, Gerb & Soffen, LLP

1180 Avenue of The Americas,
New York,
New York 10036-8403

直通電話連絡先:

Direct Telephone Calls to: (name and telephone number)
Telephone No. (212) 382-0700
Facsimile No. (212) 382-0888

唯一のまたは第一発明者の氏名 大井上 建一	Full name of sole or first inventor Kenichi Oinoue
同発明者の署名 日付	Inventor's signature Date Kenichi Oinoue Jul. 21, 2000
住所 日本国東京都	Residence Tokyo, Japan
国籍 日本	Citizenship JAPAN
郵便の宛先 日本国東京都八王子市久保山町2-3	Post Office Address C/o Intellectual Property Department, OLYMPUS OPTICAL CO., LTD.
オリンパス光学工業株式会社 知的財産部内	2-3, Kuboyama-cho, Hachioji-shi, Tokyo, Japan

(第二以降の共同発明者に対しても同様に記載し、署名をすること。)

(Supply similar information and signature for second and subsequent joint inventors.)